

A gas carburising process and an apparatus therefor

Publication number: EP0723034

Publication date: 1996-07-24

Inventor: KAWAMURA TOSHIYUKI (JP); GOI HITOSHI (JP);
MURAYAMA ATSUSHI (JP); KAMISUGI HIROFUMI (JP)

Applicant: DOWA MINING CO (JP)

Classification:

- **International:** C21D1/78; C21D9/00; C23C8/22; C21D1/64; C21D1/78;
C21D9/00; C23C8/08; C21D1/62; (IPC1-7): C23C8/22

- **European:** C21D1/78; C21D9/00K; C23C8/22

Application number: EP19950307937 19951107

Priority number(s): JP19950026144 19950120

Also published as:



US5676769 (A1)
JP8199331 (A)
EP0723034 (A3)
EP0723034 (B2)
EP0723034 (B1)

more >>

Cited documents:




US3950192
US4495004
EP0105138
GB2162208
EP0168788
more >>

[Report a data error here](#)

Abstract of EP0723034

A material to be treated (W) is preheated to a carburising temperature of 750-950 DEG C and is heat-treated in a carburising atmosphere directly supplied with hydrocarbon and oxidizing gases, in which it is heated to 1000-1100 DEG C. Then, the material being treated (W) is forcibly cooled to a temperature below 600 DEG C, the material (W) is reheated to 750-850 DEG C, and then it is hardened by quenching in oil (20), preferably using a laminar flow quenching technique.

FIG. 1



Data supplied from the esp@cenet database - Worldwide